

PBL MULTIPLE ACTIVATION JETTING TOOL

The PBL® Multiple Activation Jetting Tools utilize the same industry proven components used in the PBL Multiple Activation Bypass System. Enhanced cleanout operations are conducted through an array of jet nozzles positioned throughout the sleeve:

PBL MULTI JET JETTING TOOL

- Multiple Activation Cycles
- Multiple Jet Nozzle Options
- Multiple Sleeve Diameters
- Multiple Sleeve Blades
- Multiple Connection Options

THERE ARE SEVERAL UNIQUE FEATURES TO THIS JETTING TOOL THAT STANDOUT FROM OTHERS ON THE MARKET:

- It is a totally balanced system that is unaffected by hydrostatic pressure
- The ball shearing pressure can be set to the operator's preference
- The shear pressure can be set high to "shock" the drill pipe to aid in scale and cement removal
- The tool can be cycled multiple times in a single trip

THE PBL MULTIACTIVATED JETTING TOOL HAS MANY USES IN THE DRILLING AND COMPLETION ENVIRONMENT:

- Cleanout of BOP, risers, liner hangers and liner tops without additional pipe trips
- Increased flow rates to aid in hole cleaning during displacements
- Can be utilized in conjunction with various brush and cleanout tools for maximum riser cleanup
- When included as part of the drilling BHA, cleanouts can be conducted while tripping out of hole without rotation of drillpipe

TECHNICAL SPECIFICATIONS FOR PBL MULTI JET TOOL

Tool OD	Connection	Sleeve OD	Number of Ports ³	PBL Cycles	Drift ID
6 3/4"	4 1/2 IF	11"	12	5	1.50"
		16"	18	5	1.50"
8 1/4"	6 5/8 REG	16.25" ¹²	30	5	1.50" (2.27")
9 1/2"	7 5/8 REG	16.25" ¹²	30	5	1.50" (2.27")

¹ - Sleeve Blades coated with "casing friendly" material

² - Alternate diameters may be available

³ - All port nozzles are field changeable

